2016 Super Duty F-Series Trucks
Order Guide Supplemental Reference

8/14/15

This supplement contains Maximum Payload Charts, Snow Plow Application Charts, Cab-to-Axle dimensions and Spring Selection Charts.

This information will help you in selecting the right truck to meet your customers' needs.

Please refer to the appropriate 2016 Source Book section for more complete weight rating information.

CONTENTS

Payload Package Selection Charts

F-250 SRW Pickup	1
F-350 SRW Pickup	2
F-350 DRW Pickup	3
F-450 DRW Pickup	4
F-350 SRW Chassis Cab	5
F-350 DRW Chassis Cab	6
F-450 Chassis Cab	7
F-550 Chassis Cab	8
Snow Plow Applications Charts	9
Cab-to-Axle Dimension Chart	10

Front Spring/GAWR Selection Charts

F-250 SRW Pickup	11
F-350 SRW Pickup/Pickup Box Delete	12
F-350 DRW Pickup/Pickup Box Delete	13
F-450 DRW Pickup	14
F-350 SRW Chassis Cab	15
F-350 DRW Chassis Cab	16
F-450 Chassis Cab	17
F-550 Chassis Cab	18

2016 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-250 Pickup

GVWR (Standard)

	Cab	Regular Cab		Super Cab				Crew Cab			
	Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,040	10,000	3,700	10,000	3,600	10,000	3,490	10,000	3,380
	6.7L	10,000	3,340	10,000	3,020	10,000	2,850	10,000	2,820	10,000	2,640
4x4	6.2L	10,000	3,580	10,000	3,300	10,000	3,200	10,000	3,100	10,000	2,980
	6.7L	10,000	2,920	10,000	2,670	10,000	2,460	10,000	2,460	10,000	2,250

GVWR (Optional)

	Cab	Regular Cab		Super Cab				Crew Cab			
	Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,900	3,890	9,900	3,600	9,900	3,500	9,900	3,390	9,900	3,280
	6.7L	9,900	3,240	9,900	2,920	9,900	2,750	9,900	2,720	9,900	2,540
4x4	low application.	9,900	3,480	9,900	3,200	9,900	3,100	9,900	3,000	9,900	2,880
	6.7L	9,900	2,820	9,900	2,570	9,900	2,360	9,900	2,360	9,900	2,150

2016 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 SRW Pickup
Standard GVWR for 17" Wheel & Tire

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2 6.2L	10,000	3,920	10,000	3,630	10,200	3,760	10,200	3,650	10,500	3,810
4x2 6.7L	10,500	3,770	10,700	3,650	10,800	3,620	10,800	3,580	11,100	3,710
4x4 6.2L	10,400	3,910	10,500	3,740	10,700	3,860	10,600	3,660	10,800	3,750
4x4 6.7L	10,800	3,650	11,100	3,690	11,200	3,610	11,200	3,590	11,200	3,400

Optional Fixed GVWR

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2 6.2L	10,000	3,920	10,000	3,630	10,000	3,560	10,000	3,450	10,000	3,310
4x2 6.7L	10,000	3,270	10,000	2,950	10,000	2,820	10,000	2,780	10,000	2,610
4x4 6.2L	10,000	3,510	10,000	3,240	10,000	3,160	10,000	3,060	10,000	2,950
4x4 6.7L	10,000	2,850	10,000	2,590	10,000	2,410	10,000	2,390	10,000	2,200

ıw application. Snow Plow Package not available.

Standard Variable GVWR for 18" Wheel & Tire 4x2

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2 6.2L	10,500	4,370	10,500	4,080	10,900	4,410	10,700	4,090	11,000	4,260
4x2 6.7L	11,000	4,220	11,000	3,900	11,400	4,160	11,400	4,120	11,400	3,960
6.7L	---	---	---	---	11,500	4,260	---	---	11,500	4,050

Standard Variable GVWR for 18" Wheel & All-Season Tire 4x4

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4 6.2L	10,500	3,950	10,600	3,790	10,800	3,900	10,800	3,800	11,000	3,890
4x4 6.7L	11,000	3,790	11,200	3,740	11,300	3,660	11,300	3,640	11,300	3,440

Standard GVWR for 18" Wheel & All-Terrain Tire (inc. 20" with Diesel) 4x4

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137.0"		141.8"		158.0"		156.2"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4 6.2L	11,300	4,760	11,100	4,250	11,000	4,070	11,300	4,270	11,200	4,060
4x4 6.2L	11,100*	4,510								
4x4 6.7L	11,400	4,160	11,400	3,910	11,400	3,730	11,400	3,700	11,400	3,510
4x4 6.7L	11,500	4,260	11,500	4,000	11,500	3,820	11,500	3,800	11,500	3,610

* Camper Package only

2016 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 DRW Pickup (also includes Gasoline Pickup Box Delete)

Maximum GVWR

Cab		Regular Cab		Super Cab			Crew Cab		
Wheelbase		137.0"		158"				172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)			GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	13,500	7,050	13,900	7,000			14,000	6,870
	6.7L	14,000	6,840	14,000	6,340			14,000	6,120
4x4	6.2L	13,800	6,880	14,000	6,680			14,000	6,460
	6.7L	14,000	6,420	14,000	5,930			14,000	5,710
4x4 (Tow Boss)	6.7L							14,000	5,720

F-350 DRW Pickup Box Delete (Diesel Pickup Box Delete)

Maximum GVWR

Cab		Regular Cab		Super Cab			Crew Cab		
Wheelbase		137.0"		158"				172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)			GVWR (lbs)	Max Payload (lbs)
4x2	6.7L	13,000	6,440	13,000	5,940			13,000	5,720
4x4	6.7L	13,000	6,020	13,000	5,530			13,000	5,310

2016 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-450 DRW Pickup

GVWR (Standard)

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137"		142"		158"		156"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4 6.7L									14,000	5,300

2016 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 SRW Chassis Cab
Optional Fixed 9800 GVWR

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,800	4,320	---	---	---	---	---	---	9,800	4,024	9,800	3,775	---	---
	6.7L	9,800	3,612	---	---	---	---	---	---	9,800	3,262	9,800	2,928	---	---
4x4	6.2L	9,800	3,954	---	---	---	---	---	---	9,800	3,563	9,800	3,337	---	---
	6.7L	9,800	3,249	---	---	---	---	---	---	9,800	2,812	9,800	2,517	---	---

Standard GVWR for 18" Tires/Wheels/28-gallon Miship Fuel Tank

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,469	---	---	---	---	---	---	10,000	4,172	10,000	3,924	---	---
	6.7L	10,000	3,761	---	---	---	---	---	---	10,000	3,410	10,000	3,077	---	---
4x4	6.2L	10,000	4,103	---	---	---	---	---	---	10,000	3,712	10,000	3,485	---	---
	6.7L	10,000	3,398	---	---	---	---	---	---	10,000	2,961	10,000	2,665	---	---

Standard/Variable GVWR for 18" Tires/Wheels/40-gallon Aft-of-Axle Fuel Tank

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,200	4,723	---	---	---	---	---	---	10,600	4,644	10,700	4,496	---	---
	6.7L	11,000	4,623	---	---	---	---	---	---	11,500	4,772	11,500	4,438	---	---
4x4	6.2L	10,200	4,175	---	---	---	---	---	---	10,600	4,184	10,700	4,057	---	---
	6.7L	11,100	4,360	---	---	---	---	---	---	11,500	4,323	11,500	4,027	---	---

2016 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 DRW Chassis Cab

Standard Fixed GVWR

		Regular Cab				Super Cab		Crew Cab	
		60" CA		84" CA		60" CA		60" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	13,700	7,872	14,000	7,872	14,000	7,619	14,000	7,361
	6.7L	14,000	7,221	14,000	7,130	14,000	6,859	14,000	6,622
4x4	6.2L	14,000	7,541	14,000	7,440	14,000	7,126	14,000	6,932
	6.7L	14,000	6,796	14,000	6,700	14,000	6,404	14,000	6,200

2016 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-450 DRW Chassis Cab

Standard Fixed 16,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)
4x2	6.8L	16,500	9,945	16,500	9,815	16,500	9,575	16,500	9,486	16,500	9,523	16,500	9,269	16,500	9,325	16,500	9,197
	6.7L	16,500	9,214	16,500	9,033	16,500	8,752	16,500	8,650	16,500	8,722	16,500	8,511	16,500	8,514	16,500	8,364
4x4	6.8L	16,500	9,651	16,500	9,495	16,500	9,223	16,500	9,188	16,500	9,194	16,500	8,991	16,500	8,977	16,500	8,846
	6.7L	16,500	8,883	16,500	8,683	16,500	8,435	16,500	8,311	16,500	8,353	16,500	8,172	16,500	8,148	16,500	8,025

Optional Fixed 15,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	15,000	8,445	15,000	8,315	15,000	8,075	15,000	7,986	15,000	8,023	15,000	7,769	15,000	7,825	15,000	7,697
	6.7L	15,000	7,714	15,000	7,533	15,000	7,252	15,000	7,150	15,000	7,222	15,000	7,011	15,000	7,014	15,000	6,864
4x4	6.8L	15,000	8,151	15,000	7,995	15,000	7,723	15,000	7,688	15,000	7,694	15,000	7,491	15,000	7,477	15,000	7,346
	6.7L	15,000	7,383	15,000	7,183	15,000	6,935	15,000	6,811	15,000	6,853	15,000	6,672	15,000	6,648	15,000	6,525

Optional Fixed 16,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	16,000	9,445	16,000	9,315	16,000	9,075	16,000	8,986	16,000	9,023	16,000	8,769	16,000	8,825	16,000	8,697
	6.7L	16,000	8,714	16,000	8,533	16,000	8,252	16,000	8,150	16,000	8,222	16,000	8,011	16,000	8,014	16,000	7,864
4x4	6.8L	16,000	9,151	16,000	8,995	16,000	8,723	16,000	8,688	16,000	8,694	16,000	8,491	16,000	8,477	16,000	8,346
	6.7L	16,000	8,383	16,000	8,183	16,000	7,935	16,000	7,811	16,000	7,853	16,000	7,672	16,000	7,648	16,000	7,525

2016 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-550 DRW Chassis Cab

Standard 18,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	18,000	11,445	18,000	11,315	18,000	11,075	18,000	10,986	18,000	11,023	18,000	10,769	18,000	10,825	18,000	10,697
	6.7L	18,000	10,714	18,000	10,533	18,000	10,252	18,000	10,150	18,000	10,222	18,000	10,011	18,000	10,014	18,000	9,864
4x4	6.8L	18,000	11,151	18,000	10,995	18,000	10,723	18,000	10,688	18,000	10,694	18,000	10,491	18,000	10,477	18,000	10,346
	6.7L	18,000	10,383	18,000	10,183	18,000	9,935	18,000	9,811	18,000	9,853	18,000	9,672	18,000	9,648	18,000	9,525

Optional 17,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	17,500	10,945	17,500	10,815	17,500	10,575	17,500	10,486	17,500	10,523	17,500	10,269	17,500	10,325	17,500	10,197
	6.7L	17,500	10,214	17,500	10,033	17,500	9,752	17,500	9,650	17,500	9,722	17,500	9,511	17,500	9,514	17,500	9,364
4x4	6.8L	17,500	10,651	17,500	10,495	17,500	10,223	17,500	10,188	17,500	10,194	17,500	9,991	17,500	9,977	17,500	9,846
	6.7L	17,500	9,883	17,500	9,683	17,500	9,435	17,500	9,311	17,500	9,353	17,500	9,172	17,500	9,148	17,500	9,025

Optional 19,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	19,000	12,300														
4x4	6.8L	19,000	11,973														

Optional 19,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L			19,500	12,660	19,500	12,471	19,500	12,410	19,500	12,382	19,500	12,214	19,500	12,250	19,500	12,015
	6.7L	19,500	12,019	19,500	11,838	19,500	11,669	19,500	11,655	19,500	11,554	19,500	11,434	19,500	11,346	19,500	11,207
4x4	6.8L			19,500	12,321	19,500	12,150	19,500	12,049	19,500	12,012	19,500	11,924	19,500	11,800	19,500	11,691
	6.7L	19,500	11,709	19,500	11,524	19,500	11,343	19,500	11,294	19,500	11,235	19,500	11,102	19,500	10,993	19,500	10,877

2016 SUPER DUTY F-SERIES TRUCKS
SNOW PLOW APPLICATION CHARTS

F-250-450 4x4 Pickup/Box Delete Models (with Driver and One Passenger)

Cab Style	Wheelbase	Engine	F-250 4x4 (17")*	F-350 SRW 4x4 (18")*	F-350 DRW 4x4	F-350 DRW 4x4 (box delete)	F-450 4x4
Regular Cab	137.0"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8 Dsl	100/1005	100/1005	100/1005	100/950	X
SuperCab	141.8"	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8 Dsl	100/900	100/900	X	X	X
	158.0"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8 Dsl	100/750	100/800	100/800	100/800	X
Crew Cab	156.2"	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8 Dsl	100/800	100/800	X	X	X
	172.4"	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8 Dsl	100/700	100/700	100/700	100/650	100/650

Legend: * Considering max. **GVWR** and A/T tires. 100/750= Maximum 100 lbs. of permanently attached hardware/maximum 750 lbs. of removable plow blade and hardware. The plow and hardware weight limits are shown based upon a vehicle with 33% Ford option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows Maximum recommended values.

X = Not recommended for snow plow application. Snow Plow Package not available.

F-350 4x4 and F-450/F-550 4x2/4x4 Chassis Cab Models (with Driver and One Passenger)

Cab Style	Wheelbase/ CA	Engine	F-350 SRW 4x4	F-350 DRW 4x4 14,000-lb. GVWR	F-450 4x2 16,500-lb. GVWR	F-450 4x4 16,500-lb. GVWR	F-550 4x2 18,000-lb. GVWR	F-550 4x4 18,000-lb. GVWR	F-550+ 4x2 19,000/ 19,500-lb. GVWR	F-550+ 4x4 19,000/ 19,500-lb. GVWR
Regular Cab	140.8"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	100/1005	100/950	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	164.8"/84"	6.2L V8	X	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	X	100/900	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	188.8"/108"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	200.8"/120"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	X	X	100/1350	100/1350	100/1350	100/1300	100/1350	100/1350
Super Cab	161.8"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	100/900	100/750	100/1350	100/1350	100/1350	100/1300	100/1350	100/1300
	185.8"/84"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	X	X	100/1350	100/1300	100/1350	100/1250	100/1350	100/1250
Crew Cab	176.2"/60"	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	100/800	100/700	100/1350	100/1250	100/1350	100/1250	100/1350	100/1250
	200.2"/84"	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8 Dsl	X	X	100/1350	100/1200	100/1350	100/1150	100/1350	100/1150

Legend: 100/750= Maximum 100 lbs. of permanently attached hardware. Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The weight limits are shown based upon a vehicle with maximum buildable option content and 300 lbs for the driver and front-seat passenger (150 lbs each).
This chart ONLY shows Maximum recommended values.
X = Unavailable vehicle configuration.

2016 SUPER DUTY F-SERIES TRUCKS
CAB-TO-AXLE DIMENSION CHART

Model	Cab	Wheelbase (inches)	Cab-to-Axle (CA) (inches)	Pickup	Box Delete (1)	Chassis Cab
F-250	Reg. Cab	137	56	8' Box	Yes	--
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes	--
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes	--
F-350	Reg. Cab	137	56	8' Box	Yes	--
	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes	--
	Super Cab	162	60	--	--	Yes
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes	--
	Crew Cab	176	60	--	--	Yes
F-450	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	189	108	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Super Cab	162	60	--	--	Yes
	Super Cab	186	84	--	--	Yes
	Crew Cab	172	56	8' Box	--	--
	Crew Cab	176	60	--	--	Yes
	Crew Cab	200	84	--	--	Yes
F-550	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	189	108	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Super Cab	162	60	--	--	Yes
	Super Cab	186	84	--	--	Yes
	Crew Cab	176	60	--	--	Yes
	Crew Cab	200	84	--	--	Yes

(1) Box Delete available on 8' box only

2016 SUPER DUTY F-SERIES TRUCKS
Front Spring Selection Chart

F-250 Pickup/Pickup Box Delete

Cab Style/ Drive/WB (in)	Engine/ Transmission	Max Standard Spring Select GAWR Front (lbs.)	Heavy Duty Front Suspension Package (lbs.) (1 Up)	Camper Package (lbs.) 2 Up (4x2) 1 Up (4x4)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	---
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	---
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5000	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	5600
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2016 SUPER DUTY F-SERIES TRUCKS
Front Spring Selection Chart

F-350 SRW Pickup/Pickup Box Delete

Standard/Optional GVWR for 17" Wheel & Tire

Cab Style/ Drive/WB (in)	Engine/ Transmission	Max Standard Spring Select GAWR Front (lbs.)	Heavy Duty Front Suspension Package (lbs.) (1 Up)	Camper Package (lbs.) 2 Up (4x2) 1 Up (4x4)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5250	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	5600
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

Standard/Optional GVWR for 4x2 18" Wheel & Tire and 4x4 18"/20" Wheel & Tire

Cab Style/ Drive/WB (in)	Engine/ Transmission	Max Standard Spring Select GAWR Front (lbs.)	Heavy Duty Front Suspension Package (lbs.) 1 Up	Camper Package (lbs.) 2 Up (4x2) 1 Up (4x4)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	---
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	---
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5250	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	5600
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2016 SUPER DUTY F-SERIES TRUCKS

Front Spring Selection Chart

F-350 DRW Pickup/Pickup Box Delete[2]

The standard front spring/GAWR[1] on pickup models is computer-selected based on the total front weight of options ordered. Front spring/GAWR upgrades are in increments of 150 lbs. on 4x2 models with spring ratings from **3800 lbs.** to 5250 lbs. and in increments of 400 lbs. on 4x4 models with spring ratings from 4400 lbs. to 6000 lbs. Certain option packages include the following front spring/GAWR upgrades:

Heavy Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection 4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Front spring/GAWR upgrade is not included if the maximum front spring has been computer-selected as a consequence of options ordered.

Cab Style/ Drive/WB (in)	Engine/ Transmission	Max Standard Spring Select GAWR Front (lbs.)	Heavy-Service Suspension Package (lbs.) 1 Up	Camper Package (lbs.) 2 Up (4x2) 1 Up (4x4)	Snow Plow Package (lbs.)
Regular Cab					
4x2 - 137"	6.2L Automatic	4100	4250	4400	---
	6.7L Automatic	4700	4850	5000	---
Regular Cab					
4x4 - 137"	6.2L Automatic	4800	5200	5200	5600
	6.7L Automatic	5200	5600	5600	6000
SuperCab					
4x2 - 158"	6.2L Automatic	4550	4700	4850	---
	6.7L Automatic	5250	5250	5250	---
SuperCab					
4x4 - 158"	6.2L Automatic	5200	5600	5600	6000
	6.7L Automatic	5600	6000	6000	6000
Crew Cab					
4x2 - 172"	6.2L Automatic	4700	4850	5000	---
	6.7L Automatic	5250	5250	5250	---
Crew Cab					
4x4 - 172"	6.2L Automatic	5200	5600	5600	6000
	6.7L Automatic	5600	6000	6000	6000
	Box Delete	5940	6000	6000	6000

(1) Gross Axle Weight Rating is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVW rating or GAWR (front or rear).

(2)The spring selection process also applies to F-250 and F-350 SRW.

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2016 SUPER DUTY F-SERIES TRUCKS

FRONT SPRING SELECTION CHARTS

F-450 Pickup - Standard GVWR

Cab Style/ Drive/WB (in)	Engine	Max Standard Spring Select GAWR Front (lbs.)	Heavy-Service Suspension Package (lbs.) 1 UP	Camper Package (lbs.) 1 UP (4x4)	Snow Plow Package (lbs.)
Crew Cab 4x4 - 172"	6.7L	5940	6000	6000	6000

2016 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-350 SRW Chassis Cabs - Standard GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	9800	4100	4250	4400	---	---	---
	6.7L	9800	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	9800	4800	5200	5600	---	---	5600
	6.7L	9800	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	9800	4550	4700	4850	---	---	---
	6.7L	9800	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	9800	5200	5600	6000	----	----	6000
	6.7L	9800	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	9800	4700	4850	5000	----	----	---
	6.7L	9800	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	9800	5200	5600	6000	----	----	6000
	6.7L	9800	6000	6000	6000	6000	6000	6000

F-350 SRW Chassis Cabs - 10,000-lb. GVWR

Cab Style/ Drive/WB (in)	X = Not recommended for snow plow application. Snow	GVWR Standard/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	10,000	4100	4250	4400	---	---	---
	6.7L	10,000	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	10,000	4800	5200	5600	---	---	5600
	6.7L	10,000	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	10,000	4550	4700	4850	---	---	---
	6.7L	10,000	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	10,000	5200	5600	6000	----	----	6000
	6.7L	10,000	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	10,000	4700	4850	5000	----	----	---
	6.7L	10,000	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	10,000	5200	5600	6000	----	----	6000
	6.7L	10,000	6000	6000	6000	6000	6000	6000

F-350 SRW Chassis Cabs - Variable GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	10,200	4100	4250	4400	---	---	---
	6.7L	11,000	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	10,200	4400	4800	5200	----	----	5600
	6.7L	11,100	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	10,600	4550	4700	4850	----	----	---
	6.7L	11,500	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	10,600	5200	5600	6000	----	----	6000
	6.7L	11,500	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	10,700	4550	4700	4850	----	----	---
	6.7L	11,500	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	10,700	5200	5600	6000	----	----	6000
	6.7L	11,500	5600	6000	6000	6000	6000	6000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2016 SUPER DUTY F-SERIES TRUCKS

FRONT SPRING SELECTION CHARTS

F-350 DRW Chassis Cabs

Cab Style/ Drive/WB (in)	Engine	GVWR (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	13,700	4250	4400	4550	----	----	---
	6.7L	14,000	4850	5000	5250	5250	5250	---
Regular Cab								
4x2 - 165"	6.2L	14,000	4850	5000	5250	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	14,000	4800	5200	5600	----	----	6000
	6.7L	14,000	5200	5600	6000	6000	6000	6000
Regular Cab								
4x4 - 165"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	14,000	4700	4850	5000	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	14,000	4850	5000	5250	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2016 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-450 Chassis Cabs - Standard 16,500 lb. & Optional 16,000/15,000 lb. GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500
4x2 - 141"	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 165"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 189"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/6500/ 6000	7000/7000/ 6500	----	----	6500
4x2 - 201"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500
4x4 - 141"	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x4 - 165"	6.7L	16,500/16,000/ 15,000	6500/6500/6000	7000/7000/6500	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 189"	6.7L	16,500/16,000/ 15,000	7000/7000/6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 201"	6.7L	16,500/16,000/ 15,000	7000/7000/ 6500	7000	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 162"	6.7L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/ 6500/ 6000	7000/7000/ 6500	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 186"	6.7L	16,500/16,000/ 15,000	6500/6500/ 6000	7000/7000/ 6500	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5600/5600/5200	6000/6000/5600	6500/6500/6000	----	----	7000
4x4 - 162"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/6500/ 6000	7000/7000/ 6500	----	----	7000
4x4 - 186"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 176"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 200"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	7000
4x4 - 176"	6.7L	16,500/16,000/ 15,000	6500/6500/6000	7000/7000/6500	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 200"	6.7L	16,500/16,000/ 15,000	7000/7000/6500	7000	7000	7000	7000	7000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2016 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-550 Chassis Cabs - Standard/Optional GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.8L	18,000/17,500/ 19,000	4800/4800/ 6000	5200/5200/ 6500	5600/5600/ 7000	----	----	6500
4x2 - 141"	6.7L	18,000/17,500/ 19,500	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	6500
4x2 - 165"	6.7L	18,000/17,500/ 19,500	6000/6000/ 6500	6500/6500/ 7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6000/6000/ 6500	6500/6500/ 7000	7000	----	----	6500
4x2 - 189"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6000/6000/ 6500	6500/6500/ 7000	7000	----	----	6500
4x2 - 201"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,000	5200/5200/ 6000	5600/5600/ 6500	6000/6000/ 7000	----	----	6500/6500/7000
4x4 - 141"	6.7L	18,000/17,500/ 19,500	6000/5600/6000	6500/6000/6500	7000/6500/7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500/6500/7000
4x4 - 165"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6500/6000/ 6500	7000/6500/ 7000	7000	----	----	7000
4x4 - 189"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6500	7000	7000	----	----	7000
4x4 - 201"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	6500
4x2 - 162"	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500
4x2 - 186"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	7000
4x4 - 162"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	7000
4x4 - 186"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	6500
4x2 - 176"	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500/6500/ 7000
4x2 - 200"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	7000
4x4 - 176"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	6000	6500	7000	**----**	**----**	7000
4x4 - 200"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.